

全商品エコテックス認定



STANDARD
100

LS-17 9 10 11.5 13 15 18 20mm (UP) (LF)



LS-105 (UP) (LF)
9 10 11.5 13 15 18 20mm
COL: 01. 02. 48. 06. 09



LS-116 10 11.5 13 15 18 20mm (UP) (LF)



LS-103 (UP) (LF)
10 11.5 13 15 18 20mm
COL: 01. 02. 48. 06. 09



MS-17 9 10 11.5 mm (UP) (LF)



MS-105 9 10 11.5 mm (UP) (LF)



MS-8 (UP) (LF)



COL: 01. 02. 48. 09
9 10 11.5 mm

MS-18 (UP) (LF)



COL: 01. 02. 09
9 10 11.5 mm

MS-104 (UP) (LF)



COL: 01. 02. 48. 09
9 10 11.5 mm

MS-110 (UP) (LF)



COL: 01. 02. 48. 09
9 10 11.5 mm

MS-23 (UP) (LF)



COL: 01. 02. 09
9 10 11.5 mm

エコテックス+PETボトルリサイクル認定商品

RPB-200 (UP) (LF)



01



09

10 11.5 13 15 18 20mm

RPB-201 (UP) (LF)



01



09

10 11.5 13 15 18 20mm

RPB-17 (UP) (LF)



01



09

9 10 11.5 13 15mm

RPB-105 (UP) (LF)



01



09

10 11.5 13 15mm

耐熱性アクリル釦

PMW-17 (PMMA) (LF)



10 11.5 13 15 mm

変色せず、光沢も長期間保持します。
ポリエステル樹脂ボタンと同等の耐熱性、
耐薬品性を有します。

ポリエステルシャイン釦

SP-110 (UP) (LF)



01



09

10 11.5 13 15 mm